

DENSO PVC TAPE (COLORED)

Color Outerwrap for Denso Tapes

Description

Denso PVC Tape (Colored) is a plasticized polyvinyl chloride sheeting coated on one side with a rubber resin, pressure sensitive adhesive. Available in white, gray, blue, green, red, orange and yellow rolls.

Uses

Used as an outerwrap for Denso Petrolatum, Bitumen and Butyl Tapes. Ideal for color coding in indoor applications.

Features

- Easy to apply
- Good conformability
- Good impact resistance
- Cold applied

Application

The tape shall be spirally wrapped using a minimum 1" (25 mm) overlap on all applications. Apply sufficient tension to provide continuous adhesion of the tape.



Denso PVC Tape (Colored)

PROPERTY SPECIFICATIONS

PROPERTIES	ENGLISH	METRIC
Thickness (ASTM D1000)	6 mils	0.125 mm
Weight	.07 lbs/ft ²	.36 kg/m ²
Breaking Strength (ASTM 1000)	.21 lbf/in.	.31 kg/m
Elongation @ Break	160% min.	160% min.
Temperature Range	-22 to 175°F	-30 to 80°C
Breakdown Voltage (55% Overlap)	10 kV	10 kV
Roll Widths	2", 4", 6"	50, 100, 150 mm
Roll Length	108 ft	33 m

Quantity Estimates

Tape Width	Rolls*/ Case	Coverage with 1" (25 mm) Overlap	Coverage with 50% Overlap
		ea.	ea.
2" (50 mm)	24	200 ft ² /case (18.58 m ² /case)	200 ft ² /case (18.58 m ² /case)
4" (100 mm)	12	300 ft ² /case (27.87 m ² /case)	200 ft ² /case (18.58 m ² /case)
6" (150 mm)	8	333 ft ² /case (30.94 m ² /case)	200 ft ² /case (18.58 m ² /case)

*All rolls are 108 feet (33 m) in length.



DENSO NORTH AMERICA

Liberty Sales and Distribution, LLC

2880 Bergey Road, Suite F

Hatfield, PA 19440

Phone: (877) 373-0118

Fax: (888) 850-3787

Email: sales@libertysales.net

A Member of Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.