

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

1 Identification of the substance/mixture and of the company/undertaking

Product identifier Powercrete R-65/F1 Part A

Trade name: Powercrete R-65/F1 Part A

Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC10 Roller application or brushing

PROC11 Non industrial spraying

Environmental release category

ERC8f Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Application of the substance / the mixture Epoxy resin

Uses advised against -

Details of the supplier of the safety data sheet

Manufacturer/Supplier: Seal For Life Industries - Powercrete™

Contact details

Seal For Life Industries LLC
25 Forge Parkway, Franklin MA, 02038 USA
Tel. (+1) 800-343-7875, Fax. (+1) 800-328-4822, Email: franklin@sealforlife.com

Seal For Life Industries LLC
2320 Bowling Green Road, Franklin KY, 42134 USA
Tel. (+1) 800-343-7875, Fax. (+1) 800-328-4822, Email: franklin@sealforlife.com

Seal For Life India Private Ltd.
Plot17, GIDC Savli, Vadodara, Gujarat, Baroda, India - 391775
Tel: +91 266 726 4721, Fax: +91 266 726 4724, Email: india@sealforlife.com

Seal For Life Industries BVBA
Nijverheidsstraat 13, B-2260 Westerlo, Belgium
Tel. +32 14 72 25 00, Fax. +32 14 72 25 70, Email: belgium@sealforlife.com

Seal For Life Industries - Stopaq B.V.
Gasselterstraat 20, 9503JB Stadskanaal, the Netherlands
Tel +31 599 696 170, Fax +31 599 696 177, Email: info@sealforlife.com

Seal For Life Industries Mexico S de R.L. de C.V.
Calle 11 Norte 11002, Cd Ind Nueva Tijuana, Tijuana Baja California, Mexico, CP 22500
Tel USA: +1 858 633 9797, Tel Mx: +52 664 647 4397, Fax USA: +1 858 633 9740, Fax Mx: +52 664 607 9105
Email: mexico@sealforlife.com

Information department: Occupational product safety department of Seal For Life Industries

Emergency telephone number:

For worldwide emergency assistance call CHEMTREC (24 hours):
Within USA/Canada 1-800-424-9300; Outside USA/Canada +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

Classification of the substance or mixture



GHS08 Health hazard

Carc. 2

H351 Suspected of causing cancer. Route of exposure: Inhalation.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 1)



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS07



GHS08



GHS09

Signal word Warning

Hazard-determining components of labeling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Talc ($Mg_3H_2(SiO_3)_4$)

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P273 Avoid release to the environment.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see on this label).
P302+P352 If on skin: Wash with plenty of water.
P363 Wash contaminated clothing before reuse.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P391 Collect spillage.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not available.

(Contd. on page 3)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 2)

vPvB: Not available.

3 Composition/information on ingredients
Chemical characterization: Mixtures
Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ Skin Sens. 1, H317	25-50%
7727-43-7	barium sulphate, natural	25-50%
12001-26-2	Mica	5.0-10.0%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄) ⚠ Carc. 2, H351	2.5-5.0%
13463-67-7	titanium dioxide ⚠ Carc. 2, H351	0.1-0.5%

4 First-aid measures
Description of first aid measures
General information: Personal protection for the First Aider.

After inhalation:

Take affected persons into fresh air and keep quiet.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Information for doctor:
Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures
Extinguishing media
Suitable extinguishing agents:

 CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Advice for firefighters
Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 3)

*** 6 Accidental release measures**

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

*** 7 Handling and storage**

Handling:

Precautions for safe handling

Keep receptacles tightly sealed.

Ensure appropriate ventilation/exhaust at the workplace.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

*** 8 Exposure controls/personal protection**

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:	
7727-43-7 barium sulphate, natural	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 5* mg/m ³ *inhalable fraction; E
12001-26-2 Mica	
PEL	Long-term value: 20 mppcf ppm <1% crystalline silica
REL	Long-term value: 3* mg/m ³ *respirable dust; containing < 1% quartz
TLV	Long-term value: 3* mg/m ³ *as respirable fraction

Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 4)

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.

Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

*** 9 Physical and chemical properties**

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	Viscous
Color:	Whitish
Odor:	Light
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 260 °C (> 500 °F)
Flash point:	252 °C (486 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 300 °C (> 572 °F)

(Contd. on page 6)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 5)

Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not determined.
Density at 20 °C (68 °F):	1.92 g/cm ³ (16.022 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Segregation coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity
Reactivity No further relevant information available.

Chemical stability
Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

*** 11 Toxicological information**
Information on toxicological effects
Acute toxicity:
LD/LC50 values that are relevant for classification:
ATE (Acute Toxicity Estimates)

Oral	LD50	5212 mg/kg (rat)
Dermal	LD50	10425 mg/kg (rat)

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>4000 mg/kg (rat)
		>22000 mg/kg (rabbit)

13463-67-7 titanium dioxide

Oral	LD50	>5000 mg/kg (rat) (OECD 425)
------	------	------------------------------

(Contd. on page 7)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 6)

Dermal	LD50	>5000 mg/kg (rabbit)
--------	------	----------------------

Primary irritant effect:
on the skin: Irritant to skin and mucous membranes.

on the eye: Irritating effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

 The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant

Carcinogenic categories
IARC (International Agency for Research on Cancer)

13983-17-0	Natural wollastonite	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2B
13463-67-7	titanium dioxide	2B

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

*** 12 Ecological information**
Toxicity
Aquatic toxicity:
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

EC50/24h	3.6 mg/l (Daphnia magna)
EC50/48h	1.4-1.7 mg/l (Daphnia magna)
LC50/96h	1.5 mg/l (Fish - Oncorhynchus mykiss)
	2.4 mg/l (Fish - Brachydanio rerio)

Persistence and degradability No further relevant information available.

Behavior in environmental systems:
Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:
Remark: Toxic for fish

Additional ecological information:
General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment
PBT: Not available.

vPvB: Not available.

Other adverse effects No further relevant information available.

*** 13 Disposal considerations**
Waste treatment methods
Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015


Trade name: Powercrete R-65/F1 Part A

(Contd. of page 7)

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

*** 14 Transport information**

UN-Number DOT, ADR, IMDG, IATA	UN3082
UN proper shipping name DOT	Environmentally hazardous substances, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
ADR	3082 Environmentally hazardous substances, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
Transport hazard class(es) DOT, ADR, IMDG, IATA	
	
Class Label	9 Miscellaneous dangerous substances and articles 9
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: No limit On cargo aircraft only: No limit
Hazardous substance:	20 lbs, 9,08 kg
Remarks:	Special marking with the symbol (fish and tree).

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 8)

ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN3082, Environmentally hazardous substances, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), 9, III

*** 15 Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

7727-43-7 | barium sulphate, natural

TSCA (Toxic Substances Control Act):

25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

7727-43-7 | barium sulphate, natural

14807-96-6 | Talc (Mg3H2(SiO3)4)

13463-67-7 | titanium dioxide

Proposition 65

Chemicals known to cause cancer:

13463-67-7 | titanium dioxide

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

EPA (Environmental Protection Agency)

7727-43-7 | barium sulphate, natural

D, CBD(inh), NL(oral)

TLV (Threshold Limit Value established by ACGIH)

14807-96-6 | Talc (Mg3H2(SiO3)4)

A4

13463-67-7 | titanium dioxide

A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 | titanium dioxide

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 9)

Hazard pictograms



Signal word Warning

Hazard-determining components of labeling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
Talc ($Mg_3H_2(SiO_3)_4$)

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P273 Avoid release to the environment.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see on this label).
P302+P352 If on skin: Wash with plenty of water.
P363 Wash contaminated clothing before reuse.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P391 Collect spillage.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*** 16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Occupational product safety department of Seal For Life Industries

Contact:

Seal For Life Industries
Gasselterstraat 20, 9503JB Stadskanaal, the Netherlands
Tel: +31 599 696 170; Fax: +31 599 696 177; Email: info@sealforlife.com

Date of preparation / last revision 07/16/2015 / 3

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2015

Version 4

Reviewed on 07/16/2015

Trade name: Powercrete R-65/F1 Part A

(Contd. of page 10)

LD50: Lethal dose, 50 percent
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 2: Carcinogenicity, Hazard Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

*** Data compared to the previous version altered.**

— US —